

Specifications

Product Codes	534JN: natural gas / 534JP: propane
Product type	Direct Vent, Zero Clearance.
Input (BTU)	Natural gas: 24,000 / 6,500 Propane: 24,000 / 13,000
Vent Outlet	4 x 6-5/8" co-axial. Top or Rear outlet. Requires 817VAK.
Venting System	Co-axial 4 x 6-5/8". Co-Linear 3x3. Top outlet: Minimum 6" vertical rise. Rear outlet: Maximum horizontal without rise: 26", then minimum 12" vertical rise.
Gas convertible	Yes
Valve	GV60
Control	ValorPLUS remote control. Optional Remote Battery & Wall Switch Kit or Wall Switch Kit.
Batteries	Fireplace: Yes, in battery box; Remote control handset: Yes Optional Remote Battery & Wall Switch Kit
Electrical	Optional, to operate optional fan.
Lighting	No
Wifi	No
Fan (Blower)	¹ Optional. Operated by speed control box or hardwired with wall control. No remote.
HeatShift	No
Liners	Valor red bricks, LedgeStone, Fluted black, Reflective glass.
Fuel beds	Logs: Traditional, Driftwood. Rocks.
Fronts / Trims	Yes.
Outdoor Installation	Yes, no electrical connection allowed. Requires GV60CKO Outdoor Conversion kit.
Comments	¹ Fan operates independently from remote control.