

# Specifications

<b>Product Codes</b>	MF28JN: natural gas / MF28JP: propane
<b>Product type</b>	Direct Vent, Freestanding.
<b>Input (BTU)</b>	Natural gas: 26,000 / 6,500      Propane: 26,000 / 14,500
<b>Vent Outlet</b>	4 x 6-5/8" co-axial. Top or Rear outlet.
<b>Venting System</b>	Co-axial 4 x 6-5/8". Co-Linear 3x3. Top outlet: Minimum 24" vertical rise before elbow. Rear outlet: Maximum horizontal without rise: 24", then snorkel minimum 14" high.
<b>Gas convertible</b>	Yes
<b>Valve</b>	GV60
<b>Control</b>	ValorPLUS remote control. Optional Remote Battery & Wall Switch Kit or Wall Switch Kit.
<b>Batteries</b>	Fireplace: Yes, in battery box; Remote control handset: Yes Optional Remote Battery & Wall Switch Kit
<b>Electrical</b>	Optional, to operate optional fan.
<b>Lighting</b>	No
<b>Wifi</b>	No
<b>Fan (Blower)</b>	<sup>1</sup> Optional. Operated by speed control box or hardwired with wall control. No remote.
<b>HeatShift</b>	No
<b>Liners</b>	No
<b>Fuel beds</b>	Logs: Traditional, Driftwood, Splitwood.
<b>Fronts / Trims</b>	Traditional or Modern stove casings. Choice of colors.
<b>Outdoor Installation</b>	No
<b>Comments</b>	<sup>1</sup> Fan operates independently from remote control.