

Valor Radiant Gas Fireplace Annual Service Worksheet

Valor Dealer:	Date:
Customer Name:	
Customer Address:	Phone:
Valor Model #:	Serial #:
Install Date:	Remote Part # G6R-
Fuel Bed & Front:	Receiver Part # G6R-
Homeowner Reported Issues:	

Check	Service Point Description	Readings
☐	Perform timed thermocouple dropout test (min 20 sec).	sec
☐	Replace all batteries with fresh alkaline batteries (4 AA's in receiver and 9v in handset).	
☐	Test total voltage at receiver box – should be 6+ volts.	volts
☐	Check all gas connections for leaks with fireplace running on high.	
☐	Clean/vacuum any lint and dust build-up around valve and controls.	
☐	Inspect and clean convective hot air outlet grills or louvers.	
☐	Inspect vent terminal for soot and signs of obstructions	
☐	Remove logs/coals/rocks; vacuum lint and carbon build-up from firebox, burner and logs/coals/rocks.	
☐	Ceramic fuel bed (logs, rocks or coals) can be touched up with high temp paint.	
☐	Re-install logs/coals/rocks ensuring correct factory location spec.	
☐	Fine tune the fireplace for optimal flame appearance - burner air shutter setting and proper air restrictors installed	
☐	Clean glass of any soot buildup and whiting deposits with ammonia free glass cleaner.	
☐	Visually inspect window gasket.	
☐	Check window pressure relief spring action. Lubricate with high temp grease if stiff.	
☐	Check thermocouple millivolt reading at the red terminal on the receiver (min 8mv).	mv
☐	Check thermocouple millivolt reading at the yellow terminal on the receiver (max 2-3mv drop from red)	mv drop
☐	Check gas valve magnet dropout - measure at red terminal - shut-off gas and record valve reset	mv
☐	Check inlet pressure with manometer is to factory spec with fireplace burning on high (see rating plate).	in/wc
☐	Check manifold pressure with manometer with fireplace burning on high (see rating plate).	in/wc
☐	Check safety clearances to a combustible mantle and to room furnishings.	
☐	Check barrier screen installed correctly.	
☐	Review proper remote handset operating procedures with homeowner	
☐	Review proper location for remote handset.	
☐	Final check for smooth burning ignition, flame stability	
☐	Review results with homeowner and leave a HPBA industry brochure on Fireplace Safety.	

Notes:

Service Tech Signature:
Customer Signature: